

Product Promotion

Written by Administrator

Tuesday, 15 September 2015 07:43 - Last Updated Friday, 08 July 2016 13:52

APF – Product Standard

- APF manufactures: - UPVC pipes under various nominal pressures the specifications requested by the client based on.
 - According to ISO,ES,DIN and BS
 - High Density polyethylene (HDPE) water presser pipes for municipal and industrial transmission systems.
 - Linear low density polyethylene smooth Geomembrain are produced from prime LLDPE and LDPE as well as LDPE and HDPE resin results in
 - High quality premium grade, flexible Geomembrain sheet.

Description

Application

Advantages

Ø		UPVC pipes OD 16-630mm	and PN UP to P
---	--	------------------------	----------------

Ø		Drinking water supply
---	--	-----------------------

Ø		Sewerage systems
---	--	------------------

Product Promotion

Written by Administrator

Tuesday, 15 September 2015 07:43 - Last Updated Friday, 08 July 2016 13:52

Ø		Liquid food stuffs and industrial liquids
---	--	---

Ø		Underground irrigation system
---	--	-------------------------------

Ø		Un Attached by correct
---	--	------------------------

Ø		Excellent resistance d to Abrasion
---	--	------------------------------------

Ø		Perfect seating of network communication
---	--	--

Ø		Reduce water hanger effects
---	--	-----------------------------

Ø		Excellent hydraulic coefficient
---	--	---------------------------------

Ø		Shock resistance
---	--	------------------

Ø		No acieration
---	--	---------------

Ø		HDPE pipes OD 16-315mm and PN 6 to PN 2
---	--	---

Ø		Underground portable water Trans p
---	--	------------------------------------

Ø		Supply connections
---	--	--------------------

Product Promotion

Written by Administrator

Tuesday, 15 September 2015 07:43 - Last Updated Friday, 08 July 2016 13:52

Ø		Irrigation projects
---	--	---------------------

Ø		Industrial usage
---	--	------------------

Ø		Waste water disposal
---	--	----------------------

Ø		Chemical Transports
---	--	---------------------

Ø		Non tonic and inert in contact with water
---	--	---

Ø		Maximum hydraulics quality
---	--	----------------------------

Ø		Corrosion and abrasion resistance
---	--	-----------------------------------

Ø		Chemical and hydraulic inertia
---	--	--------------------------------

Ø		In sanctity to ground movement
---	--	--------------------------------

Ø		High mechanical resistance
---	--	----------------------------

Ø		Easy connection by welded coupling
---	--	------------------------------------

Ø		Very flexible and extremely resistance
---	--	--

Product Promotion

Written by Administrator

Tuesday, 15 September 2015 07:43 - Last Updated Friday, 08 July 2016 13:52

Ø		LLDPE Geomembran sheet	thickness 0.5mm
Ø		Prevent leakage disposal	
Ø		Irrigation systems of cants reservoir	
Ø		Water proof layer of swelling clay	and
Ø		Prevent leakage on roof top	
Ø		Diverse application	
Ø		Easy installation	
Ø		Resistant to innumerable chemical	ag
Ø		Thermal stability	
Ø		Easy transport logistics	
Ø		Zero risk in relation to microprobes	

Product Promotion

Written by Administrator

Tuesday, 15 September 2015 07:43 - Last Updated Friday, 08 July 2016 13:52

-

Description

Application

Advantages

Ø	UPVC pipes OD 16-630mm	and PN UP to P
---	------------------------	----------------

Ø	Drinking water supply
---	-----------------------

Ø	Sewerage systems
---	------------------

Ø	Liquid food stuffs and industrial liquid
---	--

Ø	Underground irrigation system
---	-------------------------------

Ø	Un Attached by correct
---	------------------------

Product Promotion

Written by Administrator

Tuesday, 15 September 2015 07:43 - Last Updated Friday, 08 July 2016 13:52

Ø		Excellent resistance d to Abrasion
---	--	------------------------------------

Ø		Perfect seating of network communica
---	--	--------------------------------------

Ø		Reduce water hanger effects
---	--	-----------------------------

Ø		Excellent hydraulic coefficient
---	--	---------------------------------

Ø		Shock resistance
---	--	------------------

Ø		No acieration
---	--	---------------

Ø		HDPE pipes OD 16-315mm and PN 6 to PN 2
---	--	---

Ø		Underground portable water Trans p
---	--	------------------------------------

Ø		Supply connections
---	--	--------------------

Ø		Irrigation projects
---	--	---------------------

Ø		Industrial usage
---	--	------------------

Ø		Waste water disposal
---	--	----------------------

Product Promotion

Written by Administrator

Tuesday, 15 September 2015 07:43 - Last Updated Friday, 08 July 2016 13:52

Ø		Chemical Transports
---	--	---------------------

Ø		Non tonic and inert in contact with water
---	--	---

Ø		Maximum hydraulics quality
---	--	----------------------------

Ø		Corrosion and abrasion resistance
---	--	-----------------------------------

Ø		Chemical and hydraulic inertia
---	--	--------------------------------

Ø		In sanctity to ground movement
---	--	--------------------------------

Ø		High mechanical resistance
---	--	----------------------------

Ø		Easy connection by welded coupling
---	--	------------------------------------

Ø		Very flexible and extremely resistance
---	--	--

Ø		LLDPE Geomembran sheet thickness 0.5mm
---	--	--

Ø		Prevent leakage disposal
---	--	--------------------------

Ø		Irrigation systems of cants reservoir
---	--	---------------------------------------

Product Promotion

Written by Administrator

Tuesday, 15 September 2015 07:43 - Last Updated Friday, 08 July 2016 13:52

Ø		Water proof layer of swelling clay an
---	--	---------------------------------------

Ø		Prevent leakage on roof top
---	--	-----------------------------

Ø		Diverse application
---	--	---------------------

Ø		Easy installation
---	--	-------------------

Ø		Resistant to innumerable chemical ag
---	--	--------------------------------------

Ø		Thermal stability
---	--	-------------------

Ø		Easy transport logistics
---	--	--------------------------

Ø		Zero risk in relation to microprobes
---	--	--------------------------------------